

## How to Order

WFC	Q3	105	K	225	000	B	R
Series	Voltage 1.	Capacitance 2.	Capacitance Tolerance 3.	Pitch 4.	Lead Length 5.	Packing 6.	Pb 7.

### 1, Voltage

Code	1H	1J	2A	2C	2D	2E	1Q	8R	2G	2H	1U	2J	1V	2K	1X
VDC	50V	63V	100V	160V	200V	250V	300V	360V	400V	500V	600V	630V	700V	800V	900V
Code	3A	1M	3B	2M	3C	3D	4Q	3G	3H	6U	5V	3K	2X	4A	6L
VDC	1000V	1100V	1250V	1300V	1600V	2000V	3000V	4000V	5000V	6000V	7500V	8000V	9000V	10000 V	12000 V
Code	B2	L5	E2	P2	Q1	Q2	Q3	R1	R2	G2	S1	S2	S8	H2	J2
VAC	125V AC	150V AC	250V AC	275V AC	300V AC	305V AC	310V AC	330V AC	350V AC	400V AC	440V AC	450V AC	475V AC	500V AC	630V AC

Note: Letter and number indicate VAC, Number and Letter indicate VDC. For example, Q1=300VAC, 1Q=300VDC  
Other Voltage Code, Please consult WEET !

### 2, Capacitance

Code	100	101	102	103	104	105	106	223	474
Values	10pF	100pF	1000pF	0.01uF	0.1uF	1uF	10uF	0.022uF	0.47uF

### 3, Capacitance Tolerance

Code	F	G	E	J	K	L	M
Tolerance	±1%	±2%	±3%	±5%	±10%	±15%	±20%

### 4, Pitch

Code	035	040	050	075	100	150	200	225	275	000
Pitch (mm)	3.5	4.0	5.0	7.5	10.0	15.0	20.0	22.5	27.5	Axial

### 5, Lead Length

Code	000	035	040	050	075	100	150	200	225	275	350	550
Length (mm)	Standard	3.5	4.0	5.0	7.5	10.0	15.0	20.0	22.5	27.5	35	55

### 6, Packing

Code	A	B	R
Packing	Ammo	Bulk	Tape Reel

### 7,Pb

Code	R
Pb	RoHS

