

WEET® PLASTIC FILM CAPACITORS

WMA MKT CL19 Metallized Polyester Film Capacitor

| | |
|------------------------|---------------------------|
| Operating Temperature: | -40°C ~ +105°C |
| Rated Voltage: | 100V, 250V, 400V, 630V.DC |
| Capacitance Range: | 0.033µF ~ 68µF |
| Capacitance Tolerance: | ±3%, ±5%, ±10% |



WMB MKT CL20 Metallized Polyester Film Capacitor

| | |
|------------------------|---------------------------|
| Operating Temperature: | -40°C ~ +105°C |
| Rated Voltage: | 100V, 250V, 400V, 630V.DC |
| Capacitance Range: | 0.01µF ~ 68µF |
| Capacitance Tolerance: | ±3%, ±5%, ±10% |



WMC MKP CBB19 Metallized Polypropylene Film Capacitor

| | |
|------------------------|-----------------------------------|
| Operating Temperature: | -55°C ~ +100°C |
| Rated Voltage: | 250V, 400V, 630V, 1000V, 1250V.DC |
| Capacitance Range: | 0.047µF ~ 56µF |
| Capacitance Tolerance: | ±3%, ±5%, ±10% |



WMD MKP CBB20 Metallized Polypropylene Film Capacitor

| | |
|------------------------|-----------------------------------|
| Operating Temperature: | -55°C ~ +100°C |
| Rated Voltage: | 250V, 400V, 630V, 1000V, 1250V.DC |
| Capacitance Range: | 0.047µF ~ 56µF |
| Capacitance Tolerance: | ±3%, ±5%, ±10% |



WME Audio Premium Metallized Polypropylene Film Capacitor

| | |
|------------------------|--------------------------------|
| Operating Temperature: | -55°C ~ +85°C |
| Rated Voltage: | 50V, 100V, 250V, 400V, 630V.DC |
| Capacitance Range: | 0.1µF ~ 100µF |
| Capacitance Tolerance: | ±2%, ±3%, ±5% 1KHz |



WMF Precise MKP Metallized Polypropylene Film Capacitor

| | |
|------------------------|--------------------------------|
| Operating Temperature: | -55°C ~ +85°C |
| Rated Voltage: | 50V, 100V, 250V, 400V, 630V.DC |
| Capacitance Range: | 0.1µF ~ 100µF |
| Capacitance Tolerance: | ±3%, ±5% 1KHz |



WMH Pure Aluminum Foil and Polypropylene Film Capacitor

| | |
|------------------------|---------------------------------|
| Operating Temperature: | -55°C ~ +85°C |
| Rated Voltage: | 100V, 200V, 400V, 600V, 630V.DC |
| Capacitance Range: | 0.01µF ~ 10µF |
| Capacitance Tolerance: | ±3%, ±5% 1KHz |



WMW Pure Copper Foil and Polypropylene Film Capacitor

| | |
|------------------------|---------------------------|
| Operating Temperature: | -55°C ~ +85°C |
| Rated Voltage: | 100V, 200V, 400V, 600V.DC |
| Capacitance Range: | 0.1µF ~ 3.3µF |
| Capacitance Tolerance: | ±3%, ±5% 1KHz |



WFA CL21 MKT Metallized Polyester Film Capacitor

| | |
|------------------------|---------------------------|
| Operating Temperature: | -40°C ~ +85°C |
| Rated Voltage: | 100V, 250V, 400V, 630V.DC |
| Capacitance Range: | 0.01µF ~ 6.8µF |
| Capacitance Tolerance: | ±5%, ±10%, ±20% |



WFB CBB21 MKP Metallized Polypropylene Film Capacitor

| | |
|------------------------|---------------------------|
| Operating Temperature: | -40°C ~ +85°C |
| Rated Voltage: | 100V, 250V, 400V, 630V.DC |
| Capacitance Range: | 0.01µF ~ 10µF |
| Capacitance Tolerance: | ±5%, ±10%, ±20% |



WFC X2 Metallized Polypropylene Film Capacitor

| | |
|------------------------|-------------------|
| Operating Temperature: | -40°C ~ +110°C |
| Rated Voltage: | 310VAC |
| Capacitance Range: | 0.0047µF ~ 10.0µF |
| Capacitance Tolerance: | ±10% (K) |



WFD CL21B MKT Metallized Polyester Film Capacitor

| | |
|------------------------|--------------------------------------|
| Operating Temperature: | -40°C ~ +85°C |
| Rated Voltage: | 63V, 100V, 160V, 250V, 400V, 630V.DC |
| Capacitance Range: | 0.001µF ~ 2.2µF |
| Capacitance Tolerance: | ±5%, ±10%, ±20% |



WFE CBB21B MKP Metallized Polypropylene Film Capacitor

| | |
|------------------------|---------------------|
| Operating Temperature: | -40°C ~ +85°C |
| Rated Voltage: | 250V, 400V, 630V.DC |
| Capacitance Range: | 0.0047µF ~ 3.9µF |
| Capacitance Tolerance: | ±5%, ±10%, ±20% |



WFF CBB61 Motor Running Capacitor

| | |
|------------------------|-----------------|
| Operating Temperature: | -40°C ~ +85°C |
| Rated Voltage: | 250V, 450V.AC |
| Capacitance Range: | 1µF ~ 20µF |
| Capacitance Tolerance: | ±5%, ±10%, ±20% |



WFG CL23B Mini Box Metallized Polyester Film Capacitor

| | |
|------------------------|-------------------------------------|
| Operating Temperature: | -40°C ~ +100°C |
| Rated Voltage: | 50V, 63V, 100V, 250V, 400V, 630V.DC |
| Capacitance Range: | 0.001µF ~ 2.2µF |
| Capacitance Tolerance: | ±5%, ±10%, ±20% |



WFK MMKP82 Double Sided Metallized Polypropylene Capacitor

| | |
|------------------------|--|
| Operating Temperature: | -40°C ~ +105°C |
| Rated Voltage: | 250V, 400V, 630V, 1000V, 1600V, 2000V.DC |
| Capacitance Range: | 0.00022µF ~ 3.9µF |
| Capacitance Tolerance: | ±2%(G), ±3%(H), ±5%(J), ±10%(K), ±20%(M) |



WEET® ALUMINUM ELECTROLYTIC CAPACITORS

WAA 85°C 2000H Polarized Aluminum Electrolytic Capacitors

| | |
|------------------------|------------------|
| Operating Temperature: | -40°C ~ +85°C |
| Rated Voltage: | 6.3V ~ 450V.DC |
| Capacitance Range: | 1µF ~ 10000µF |
| Capacitance Tolerance: | ±10%(K), ±20%(M) |



WAB 105°C 1000H Polarized Aluminum Electrolytic Capacitors

| | |
|------------------------|------------------|
| Operating Temperature: | -40°C ~ +105°C |
| Rated Voltage: | 6.3V ~ 450V.DC |
| Capacitance Range: | 1µF ~ 4700µF |
| Capacitance Tolerance: | ±10%(K), ±20%(M) |



WMM Bi-polar Aluminum Electrolytic Capacitors for Audio

| | |
|------------------------|----------------|
| Operating Temperature: | -40°C ~ +105°C |
| Rated Voltage: | 50V, 100V.DC |
| Capacitance Range: | 1µF ~ 150µF |
| Capacitance Tolerance: | ±10% |
| Dissipation Factor: | MAX 5% at 1KHz |



WMS Non-polar Aluminum Electrolytic Capacitors for Audio

| | |
|------------------------|-----------------|
| Operating Temperature: | -40°C ~ +105°C |
| Rated Voltage: | 50V, 100V.DC |
| Capacitance Range: | 1µF ~ 470µF |
| Capacitance Tolerance: | ±10% |
| Dissipation Factor: | MAX 10% at 1KHz |



WMN BP NP Aluminum Electrolytic Capacitors For Audio

| | |
|------------------------|-------------------|
| Operating Temperature: | -40°C ~ +105°C |
| Rated Voltage: | 50V, 100V.DC |
| Capacitance Range: | 47µF ~ 1000µF |
| Capacitance Tolerance: | ±10% |
| Dissipation Factor: | MAX 10% at 120KHz |



WPA SMD Polymer Aluminum Solid Electrolytic Capacitors

| | |
|------------------------|---------------------|
| Operating Temperature: | -55°C ~ +105°C |
| Rated Voltage: | 2.5V ~ 100V.DC |
| Capacitance Range: | 10µF ~ 2200µF |
| Capacitance Tolerance: | ±20% at 120Hz, 20°C |



WPB Radial Polymer Aluminum Solid Electrolytic Capacitors

| | |
|------------------------|---------------------|
| Operating Temperature: | -55°C ~ +105°C |
| Rated Voltage: | 2.5V ~ 25V.DC |
| Capacitance Range: | 68µF ~ 2200µF |
| Capacitance Tolerance: | ±20% at 120Hz, 20°C |



WEA 85°C 2000H Snap in Aluminum Electrolytic Capacitors

| | |
|------------------------|---|
| Operating Temperature: | 10V~400V: -40°C~+85°C, 450V~500V: -25°C~+85°C |
| Rated Voltage: | 10V ~ 500V.DC |
| Capacitance Range: | 47µF ~ 68000µF |
| Capacitance Tolerance: | ±20% at 120Hz, 20°C |



WEB 105°C 2000H Snap in Aluminum Electrolytic Capacitors

| | |
|------------------------|--|
| Operating Temperature: | -40°C ~ +105°C (>160V: -25°C ~ +105°C) |
| Rated Voltage: | 16V ~ 500V.DC |
| Capacitance Range: | 39µF ~ 47000µF |
| Capacitance Tolerance: | ±20% at 120Hz, 20°C |



WEC 85°C 5000H Snap in Aluminum Electrolytic Capacitors

| | |
|------------------------|--|
| Operating Temperature: | 10V~400V: -40°C+85°C, 450V~500V: -25°C~+85°C |
| Rated Voltage: | 10V ~ 500V.DC |
| Capacitance Range: | 47µF ~ 68000µF |
| Capacitance Tolerance: | ±20% at 120Hz, 20°C |



WED 85°C 2000H Screw Aluminum Electrolytic Capacitors

| | |
|------------------------|--------------------------------------|
| Operating Temperature: | -40°C ~ +85°C (315WV, -25°C ~ +85°C) |
| Rated Voltage: | 16V - 500V.DC |
| Capacitance Range: | 270µF ~ 820000µF |
| Capacitance Tolerance: | ±20% at 120Hz, 20°C |



WEF 105°C 2000H Screw Aluminum Electrolytic Capacitors

| | |
|------------------------|--|
| Operating Temperature: | 25V~100V: -40°C+105°C, 160V~450V: -25°C~+105°C |
| Rated Voltage: | 25V ~ 450V.DC |
| Capacitance Range: | 220µF ~ 330000µF |
| Capacitance Tolerance: | ±20% at 120Hz, 20°C |



WEG Lug Aluminum Electrolytic Capacitors For Photo Flash

| | |
|------------------------|---------------------------------|
| Operating Temperature: | -20°C ~ +55°C |
| Rated Voltage: | 330V.DC 360V.DC 400V.DC 450V.DC |
| Capacitance Range: | 180µF ~ 1500µF |
| Capacitance Tolerance: | -10% ~ +20% (20°C, 120Hz) |



WEH 85°C 2000H Lug Aluminum Electrolytic Capacitors

| | |
|------------------------|-----------------------------|
| Operating Temperature: | -40°C ~ +85°C -25°C ~ +85°C |
| Rated Voltage: | 10V ~ 100V.DC 160 ~ 450V.DC |
| Capacitance Range: | 47µF ~ 22000µF |
| Capacitance Tolerance: | ±20% (120Hz, 20°C) |



WVT 105°C 2000H SMD Aluminum Electrolytic Capacitors

| | |
|------------------------|------------------------------------|
| Operating Temperature: | -40°C ~ +105°C |
| Rated Voltage: | 4V ~ 100V.DC |
| Capacitance Range: | 0.1µF ~ 10000µF |
| Capacitance Tolerance: | ±20% at 120Hz, 20°C |
| Certifications: | ISO 9001; RoHS; REACH Halogen Free |



Various Dimensions mm: 4x5.4, 5x5.4, 6.3x5.4, 6.3x7.7, 8x10.5, 10x10.5, 10x13.5, 12.5x13.5, 12.5x16, 16x16.5, 16x21.5



WEET® CERAMIC CAPACITORS

WSY X1 Y1 CD 400VAC Safety Recognized Capacitors

| | |
|------------------------|---------------------------|
| Operating Temperature: | -25°C ~ +85°C |
| Rated Voltage: | AC 125V, 250V, 300V, 400V |
| Capacitance Range: | 10pF ~ 10000pF |
| Capacitance Tolerance: | ±10%, ±20%, +80% ~ -20% |



WSY X1 Y2 CE 300VAC Safety Recognized Capacitors

| | |
|------------------------|---------------------------|
| Operating Temperature: | -25°C ~ +85°C |
| Rated Voltage: | AC 125V, 250V, 300V, 400V |
| Capacitance Range: | 10pF ~ 10000pF |
| Capacitance Tolerance: | ±10%, ±20%, +80% ~ -20% |



WCA Radial High Voltage Disc Ceramic Capacitors

| | |
|------------------------|---------------------------|
| Operating Temperature: | -25°C ~ +85°C |
| Rated Voltage: | 1KV ~ 25KV DC |
| Capacitance Range: | 100pF ~ 10000pF |
| Capacitance Tolerance: | ±5%, ±10%, ±20%, +80%-20% |



WCB Radial Multilayer Monolithic Ceramic Capacitors

| | |
|------------------------|---|
| Operating Temperature: | NPO (COG) X7R: -55°C ~ +125°C, Y5V (Z5U): -25°C ~ +85°C |
| Rated Voltage: | DC 25V, 50V, 100V |
| Capacitance Range: | 0.5pF ~ 22µF |
| Capacitance Tolerance: | ±5%, ±10%, ±20% |
| Pitch Size: | 2.54mm, 5.08mm, 7.5mm |



WCC Axial Multilayer Monolithic Ceramic Capacitors

| | |
|------------------------|---|
| Operating Temperature: | NPO (COG) X7R: -55°C ~ +125°C, Y5V (Z5U): -25°C ~ +85°C |
| Rated Voltage: | DC 25V, 50V, 100V |
| Capacitance Range: | 1pF ~ 1µF |
| Capacitance Tolerance: | ±5%, ±10%, ±20% |



WCD Chip SMD MLCC Multilayer Ceramic Capacitors

| | |
|------------------------|---|
| Operating Temperature: | NPO (COG) X7R: -55°C ~ +125°C, Y5V (Z5U): -30°C ~ +85°C |
| Rated Voltage: | 16 VDC, 25 VDC, 50 VDC, 63 VDC |
| Capacitance Range: | 0.5pF ~ 10µF |
| Capacitance Tolerance: | ±0.1pF, ±0.25pF, ±0.5pF, ±5.0%, ±10%, ±20%, +80% ~ -20% |
| Size Code: | 0402, 0603, 0805, 1206, 1210, 1812, 2220 |



WEET® TANTALUM CAPACITORS

WTA CA42 Radial Epoxy Dipped Tantalum Capacitors

| | |
|------------------------|---|
| Operating Temperature: | -55°C ~ +125°C; >85°C (with rated voltage derating) |
| Rated Voltage: | 6.3V, 10V, 16V, 25V, 35V, 50V |
| Capacitance Range: | 0.1µF ~ 1000µF |
| Capacitance Tolerance: | K: ±10%; M: ±20% (Standard) |
| Pitch Size: | 2.54mm, 5.08mm |



WTB CA45 SMD Chip Tantalum Capacitors Standard

| | |
|------------------------|---|
| Operating Temperature: | -55°C ~ +125°C; >85°C (with rated voltage derating) |
| Rated Voltage: | 4V, 6.3V, 10V, 16V, 20V, 25V, 35V, 40V, 50V, 63V, 75V, 100V |
| Capacitance Range: | 0.1µF ~ 1000µF |
| Capacitance Tolerance: | K: ±10%; M: ±20% (Standard) |
| Case Size: | A, B, C, D, E case |



WTC CA45